

PLAT OF SURVEY

U.S. GOVERNMENT LAND

BEING THE TOWNSHIP LINE FROM THE SOUTH SECTION CORNER TO SECTIONS 34 AND 35, TOWNSHIP 7 NORTH, RANGE 1 EAST, TO THE NORTH SECTION CORNER TO SECTIONS 5 AND 6, TOWNSHIP 6 NORTH, RANGE 2 EAST, SECOND PRINCIPAL MERIDIAN, LAWRENCE AND MONROE COUNTIES, INDIANA.

REPORT OF SURVEY

THIS SURVEY WAS MADE FOR THE U.S. DEPARTMENT OF AGRICULTURE, FOREST SERVICE, FOR THE MONUMENTING AND MARKING OF THE TOWNSHIP LINE.

THE ORIGINAL SURVEYS WERE CONDUCTED BY ARTHUR HENRIE AND ALEXANDER HOLMES IN 1811. SUBSEQUENT SURVEYS WERE BY COUNTY SURVEYORS IN 1856, 1859, 1878 AND 1911 AND ARE ON FILE IN THE COUNTY SURVEYOR'S OFFICES IN BEDFORD, INDIANA AND BLOOMINGTON, INDIANA. A SUBSEQUENT SURVEY WAS PERFORMED BY THE FOREST SERVICE IN 1943 AND IS ON FILE AT THE WAYNE-HOOSIER NATIONAL FOREST OFFICE AT BEDFORD, INDIANA.

PRIOR TO MAKING THIS SURVEY, I REVIEWED THE ORIGINAL AND SUBSEQUENT SURVEY NOTES. I CONSULTED ADJOINING LANDOWNERS, LOCAL RESIDENTS, COUNTY SURVEYORS AND FOREST SERVICE PERSONNEL FOR INFORMATION PERTAINING TO THE LOCATION OF CORNERS NEEDED FOR THIS SURVEY.

THE CORNERS RECOVERED, RESTORED AND ESTABLISHED BY THIS SURVEY ARE MARKED IN THE LEGEND. THE BEARINGS BETWEEN MONUMENTS ARE TRUE MERIDIAN AS DETERMINED BY SOLAR OBSERVATIONS TAKEN ON MARCH 25, 1986 NEAR THE NORTH SECTION CORNER TO SECTIONS 1 AND 2, TOWNSHIP 6 NORTH, RANGE 2 EAST, AND APRIL 18, 1986 NEAR THE 1/4 CORNER TO SECTIONS 5 AND 6, TOWNSHIP 6 NORTH, RANGE 2 EAST. THE RANDOM CONTROL TRAVERSE FOR THIS SURVEY BEING 5 MILES IN LENGTH, WITH AN ANGULAR CLOSURE OF 17 SECONDS.

EACH MONUMENTED CORNER POSITION IS REFERENCED TO BLAZED AND SCRIBED BEARING TREES AND/OR DESCRIBED REFERENCE OBJECTS, EXCEPT AS OTHERWISE NOTED. ALL MONUMENTED CORNERS HAVE EITHER A STONE, ALUMINUM PIPE OR STEEL PIN AT THE CORNER POSITION.

A MORE COMPLETE DESCRIPTION OF EACH MONUMENTED CORNER CAN BE FOUND ON THE CERTIFIED LAND CORNER RESTORATION FORM. THESE FORMS ARE ON FILE AT THE WAYNE-HOOSIER NATIONAL FOREST OFFICE AT BEDFORD, INDIANA AND AT THE BROWNSTOWN RANGER DISTRICT OFFICE AT BROWNSTOWN, INDIANA AND IN THE MONROE COUNTY SURVEYOR'S OFFICE IN BLOOMINGTON, INDIANA AND IN THE LAWRENCE COUNTY SURVEYOR'S OFFICE IN BEDFORD, INDIANA.

CORNERS RECOVERED

1. SOUTH SECTION CORNER TO SECTIONS 34 AND 35, T 7 N, R 1 E
RECOVERED STANDARD FOREST SERVICE MONUMENT FROM PRIOR SURVEYS.
2. NORTH SECTION CORNER TO SECTIONS 1 AND 2, T 6 N, R 1 E
RECOVERED STANDARD INDIANA STATE HIGHWAY COMMISSION MONUMENT AS PERPETUATED BY I.S.H.C. DURING CONSTRUCTION OF INDIANA STATE HIGHWAY #446.
3. PROPERTY DIVISION, NORTH LINE SECTION 6, T 6 N, R 2 E
RECOVERED STONE AS MONUMENTED IN 1943 SURVEY BY FOREST SERVICE. SET AS NORTH QUARTER CORNER SECTION 6.
4. PROPERTY DIVISION, NORTH LINE SECTION 6, T 6 N, R 2 E
RECOVERED STONE AS MONUMENTED IN 1943 SURVEY BY FOREST SERVICE.

CORNERS RECOVERED AND REMONUMENTED

5. SOUTH SECTION CORNER TO SECTIONS 31 AND 32, T 7 N, R 2 E
RECOVERED STONE AS MONUMENTED IN 1856 AND RECOVERED AND REMONUMENTED BY 1911 SURVEY. REPLACED THE STONE WITH AN ALUMINUM MONUMENT AND BURIED THE STONE BESIDE THE PIPE. CORNER ACCESSORIES ESTABLISHED:
B. GUM 8", S 5° W, 3.7'
W. OAK 9", S 72° W, 40.5'

PLAT OF SURVEY

U.S. GOVERNMENT LAND

BEING THE TOWNSHIP LINE FROM THE SOUTH SECTION CORNER TO SECTIONS 34 AND 35, TOWNSHIP 7 NORTH, RANGE 1 EAST, TO THE NORTH SECTION CORNER TO SECTIONS 5 AND 6, TOWNSHIP 6 NORTH, RANGE 2 EAST, SECOND PRINCIPAL MERIDIAN, LAWRENCE AND MONROE COUNTIES, INDIANA.

CORNERS RESTORED

6. TOWNSHIP CORNER SECTIONS 1, T 6 N, R 1 E, SECTION 6, T 6 N, R 2 E, SECTION 36, T 7 N, R 1 E AND SECTION 31, T 7 N, R 2 E

NO EVIDENCE OF A CORNER MONUMENT WAS RECOVERED. CORNER POSITION RESTORED ON TOWNSHIP CORNER AT RECORD PROPORTIONAL DISTANCE FROM RECOVERED SOUTH SECTION CORNER TO SECTIONS 31 AND 32, T 7 N, R 2 E AND RECOVERED NORTH SECTION CORNER TO SECTIONS 1 AND 2, T 6 N, R 1 E. SET 1/2" STEEL PIN WITH 1 1/2" ALUMINUM CAP. UNMARKED CORNER ACCESSORIES ESTABLISHED:

ALUMINUM WITNESS MONUMENT, S 89° 47' 54" E, 66.0'
SYCAMORE 11", EAST 47.7'
BLUE BEECH 8", S 67° E, 38.8'
SYCAMORE 14", S 29° E, 46.2'
BLACK CHERRY 12", S 40° W, 73.4'

7. NORTH SECTION CORNER TO SECTIONS 5 AND 6, T 6 N, R 2 E

NO EVIDENCE OF A CORNER MONUMENT WAS RECOVERED. CORNER POSITION RESTORED ON TOWNSHIP LINE AT RECORD OFFSET DISTANCE FROM RECOVERED CORNER STONE FOR SOUTH SECTION CORNER, SECTIONS 31 AND 32, T 7 N, R 2 E. SET ALUMINUM MONUMENT. CORNER ACCESSORIES ESTABLISHED:

W. OAK 9", N 80° W, 16.9'
W. OAK 15", S 24° E, 20.5'

8. SOUTH QUARTER CORNER TO SECTION 31, T 7 N, R 2 E

NO EVIDENCE OF A CORNER MONUMENT WAS RECOVERED. CORNER POSITION RESTORED ON TOWNSHIP LINE AT RECORD PROPORTIONAL DISTANCE FROM RECOVERED SOUTH SECTION CORNER TO SECTIONS 31 & 32, T 7 N, R 2 E, AND TOWNSHIP CORNER T 7 N, R 2 E - T 7 N, R 1 E. SET ALUMINUM MONUMENT. CORNER ACCESSORIES ESTABLISHED:

SUGAR MAPLE 12", S 3° W, 25.6'
SUGAR MAPLE 9", N 89° E, 34.7'

9. EAST SIXTEENTH IN THE SOUTH LINE OF SECTION 31, T 7 N, R 2 E

NO EVIDENCE OF A CORNER MONUMENT WAS RECOVERED. CORNER POSITION RESTORED ON TOWNSHIP LINE AT RECORD PROPORTIONAL DISTANCE FROM SOUTH QUARTER CORNER SECTION 31, T 7 N, R 2 E AND SOUTH SECTION CORNER SECTIONS 31 & 32, T 7 N, R 2 E. SET ALUMINUM MONUMENT. CORNER ACCESSORIES ESTABLISHED:

BEECH 4", S 75° E, 13.6'
SUGAR MAPLE 8", NORTH, 2.2'

10. SOUTH SECTION CORNER TO SECTION 35 AND 36, T 7 N, R 1 E

NO EVIDENCE OF A CORNER MONUMENT WAS RECOVERED. CORNER POSITION RESTORED ON TOWNSHIP LINE AT RECORD OFFSET DISTANCE FROM RECOVERED CORNER MONUMENT FOR NORTH SECTION CORNER, SECTIONS 1 AND 2, T 6 N, R 1 E. SET ALUMINUM MONUMENT. UNMARKED CORNER ACCESSORIES ESTABLISHED:

WALNUT 22", S 82° W, 54.1'
N. E. CORNER OF BARN, N 78° W, 150.6'
I.S.H.C. R/W MONUMENT, N 59° W, 72.6'

11. QUARTER CORNER TO SECTION 1, T 6 N, R 1 E AND SECTION 36, T 7 N, R 1 E

NO EVIDENCE OF A CORNER MONUMENT WAS RECOVERED. CORNER POSITION RESTORED ON TOWNSHIP LINE EQUIDISTANCE FROM TOWNSHIP CORNER AND SOUTH SECTION CORNER TO SECTIONS 35 AND 36, T 7 N, R 1 E. SET ALUMINUM MONUMENT. UNMARKED CORNER ACCESSORIES ESTABLISHED:

MOCKERNUT HICKORY 23", S 68° W, 46.5'
MOCKERNUT HICKORY 20", N 37° W, 22.9'
MOCKERNUT HICKORY 13", S 05° E, 28.8'

12. EAST SIXTEENTH TO SECTION 1, T 6 N, R 1 E & SECTION 36, T 7 N, R 1 E

NO EVIDENCE OF A CORNER MONUMENT WAS RECOVERED. CORNER POSITION RESTORED ON TOWNSHIP LINE EQUIDISTANCE FROM TOWNSHIP CORNER AND QUARTER CORNER TO SECTION 36, T 7 N, R 1 E, AND SECTION 1, T 6 N, R 1 E. SET ALUMINUM MONUMENT. UNMARKED CORNER ACCESSORIES ESTABLISHED:

ASH 11", S 25° E, 43.3'
SUGAR MAPLE 11", N 2° W, 47.2'

PLAT OF SURVEY

U.S. GOVERNMENT LAND

BEING THE TOWNSHIP LINE FROM THE SOUTH SECTION CORNER TO SECTIONS 34 AND 35, TOWNSHIP 7 NORTH, RANGE 1 EAST, TO THE NORTH SECTION CORNER TO SECTIONS 5 AND 6, TOWNSHIP 6 NORTH, RANGE 2 EAST, SECOND PRINCIPAL MERIDIAN, LAWRENCE AND MONROE COUNTIES, INDIANA.

CORNERS RESTORED (CONTINUED)

13. WEST SIXTEENTH IN THE NORTH LINE SECTION 1, T 6 N, R 1 E

NO EVIDENCE OF A CORNER MONUMENT WAS RECOVERED. CORNER POSITION RESTORED ON TOWNSHIP LINE EQUIDISTANCE FROM QUARTER CORNER TO SECTION 1, T 6 N, R 1 E, AND SECTION 36, T 7 N, R 1 E, AND NORTH SECTION CORNER TO SECTIONS 1 AND 2, T 6 N, R 1 E. SET ALUMINUM MONUMENT. UNMARKED CORNER ACCESSORIES ESTABLISHED:

BITTERNUT HICKORY 10", S 56° W, 11.0'
SUGAR MAPLE, 5", N 71° W, 12.2'
SUGAR MAPLE 5", N 42° E, 7.3'
CHINQUAPIN OAK 14", S 62° E, 26.3'

14. SOUTH QUARTER CORNER TO SECTION 35, T 7 N, R 1 E

NO EVIDENCE OF A CORNER MONUMENT WAS RECOVERED. CORNER POSITION RESTORED ON TOWNSHIP LINE EQUIDISTANCE FROM SOUTH SECTION CORNER TO SECTION 35 AND 36, T 7 N, R 1 E AND SOUTH SECTION CORNER TO SECTION 34 AND 35, T 7 N, R 1 E. SET ALUMINUM MONUMENT. UNMARKED CORNER ACCESSORIES ESTABLISHED:

SUGAR MAPLE 9", N 38° E, 18.7'
SUGAR MAPLE 11", N 70° E, 39.5'
SUGAR MAPLE 13", N 88° W, 49.6'
SUGAR MAPLE 13", S 56° W, 44.2'

15 PROPERTY CORNER IN SOUTH LINE SECTION 35, T 7 N, R 1 E

SET ALUMINUM IN TOWNSHIP LINE AS SOUTHEAST CORNER OF PARCEL NO. 929. UNMARKED CORNER ACCESSORIES ESTABLISHED:

BITTERNUT HICKORY 12", N 75° E, 25.8'
BLUE BEECH 6", N 28° W, 14.9'
POPLAR 24", SOUTH, 8.2'
WOOD FENCE POST, N 35° W, 0.8'


COPIES OF THE FIELD NOTES AND PLAT ARE ON FILE AT THE WAYNE-HOOSIER NATIONAL FOREST OFFICE AT BEDFORD, INDIANA AND AT THE BROWNSTOWN RANGER DISTRICT OFFICE AT BROWNSTOWN, INDIANA. THE CONTROL TRAVERSE FOR THIS SURVEY WAS MEASURED BY ELECTRONIC MEASURING EQUIPMENT.

SURVEYOR'S AFFIDAVIT

I, VICTOR H. McCAULEY, PROFESSIONAL LAND SURVEYOR, REGISTERED BY THE LAWS OF THE STATE OF INDIANA, HEREBY CERTIFY THAT I HAVE SURVEYED AND MONUMENTED THE TOWNSHIP LINE FROM THE SOUTH SECTION CORNER TO SECTIONS 34 AND 35, TOWNSHIP 7 NORTH, RANGE 1 EAST, TO THE NORTH SECTION CORNER TO SECTIONS 5 AND 6, TOWNSHIP 6 NORTH, RANGE 2 EAST, SECOND PRINCIPLE MERIDIAN, LAWRENCE AND MONROE COUNTIES, INDIANA, IN ACCORDANCE WITH THE RULES FOR SURVEYS OF PUBLIC LANDS AND THE STATUTES OF THE STATE OF INDIANA, ALL TO THE BEST OF MY KNOWLEDGE AND BELIEF.

THE PLAT MAP AND SURVEY NOTES ARE AN ACCURATE REPRESENTATION OF THE CORNERS RECOVERED, RESTORED AND ESTABLISHED. DATE OF SURVEY, October 31, 1986.

Victor H. McCauley
VICTOR H. McCAULEY, INDIANA L.S. #S0336



April 4th
A.D. 1836
Ran the
following
lines and made
the following
corners in
Section No
35 T 7 R
1 E for
Rosannah



Christianburg
Michael Warner
Peter Varman James Mathes and
James Clark Beginning at (A) it being
the northern $\frac{1}{2}$ mile post of said section
Then west with the section line 80 Poles to
(B) witness trees

Sugar 8 inches in diameter S 25° W 11 lks distant
Dogwood 8 " " " " N 61° E 14 " "

Then S 6° E 280 Poles and 21 links to (C) wit trees
White oak 24 inches in diameter N 14° E 32 lks dist.
S Walnut 10 " " " " S 64° W 29 " "

Then S 6° E 80 Poles and 7 links to (D) wit trees
Black gum 20 inches in diameter S 45° W 63 lks dist
Black oak 4 " " " " S 22° E 26 " "

Then west 83 Poles to (E) witness trees
Spanish oak 13 inches in diameter N 33° W 33 lks dist
Maple 12 " " " " S 34° W 6 $\frac{1}{2}$ " "

Witness trees made at (F) center of section 35
Black Ash 6 inches in diameter N 62° W 19 $\frac{1}{2}$ lks dist
Hickory 6 " " " " S 28° E 22 $\frac{1}{2}$ " "

Witness trees west of center 80 Poles at (B)
Hickory 15 inches in diameter S 33° E 18 lks dist
" 8 " " " " N 74° W 12 " "

Length of the line from S.E. corner to
the S.W. corner 332 Poles

Benjamin Murphy and
Isaac Hatfield Chain bearers
Sworn This April 4th A.D. 1836

(It appears there is a contradiction
in all this record, I think however
the lettering is correct and description
of line reads backwards all the
time M H B,
James W. Spencer
M C Surveyor